



ECOSHIELD
TO A BETTER FUTURE



 Contact information

Finland Office: Vanha, Helsingintie, 18 B00700 Helsinki, Finland, Helsinkiranta, Finland

Iraq Office: EcoShield Building, Al Senaha St, Baghdad, Baghdad Governorate

 **Info@ecoshieldfi.com**
power@ecoshieldfi.com

 **www.ecoshieldfi.com**



FINLAND HYBRID SOLAR INVERTER

Solar Inverter System




ES-HY3.6KW



Features:

- Grid-tie with backup+Off-Grid
- Built-in MPPT solar charge controller
- High PV input voltage range 60-450V
- Configurable AC/solar priority via LCD settings
- Inverter can operate without battery
- Smart battery charging design optimizes battery life
- WiFi APP monitoring optional
- High efficiency, low no-load loss
- BMS communication port



Home energy storage system

Specification

Model		ES-HY3.6KW
Rated battery voltage		24VDC
Inverter output	Rated power	3600W
	Peak power	7200W
	Waveform	Pure Sine Wave
	AC voltage (Battery mode)	(220vac~240vac)±5% 230vac(Default)
	Inverter efficiency(Max)	93%
	Transfer time	10ms(UPS) 、20ms(APL)
	No load power consumption	<30W@ 24VDC
AC input	Voltage	230VAC
	Selectable voltage range	170~280VAC(UPS) 90~280VAC(APL)
	Frequency range	50Hz / 60Hz (Auto sensing)
Battery	Battery voltage	24VDC
	Floating charging voltage	27VDC
	Overcharge protection voltage	29.2VDC
Solar charger & AC charger	Solar charger type	MPPT
	MPPT Max. PV array power	4000W
	MPPT output voltage range	60-450V
	Max.PV array open circuit voltage	500V
	Maximum solar charge current	80A
	Maximum AC charge current	80A
	Maximum charge current	80A
Physical	Dimensions D*W*H(mm)	334*309*109
	Package Size D*W*H(mm)	452*395*190
	Net weight(kg)	8.3
	Gross weight(kg)	9.3
Environment	Humidity	5% to 95% relative humidity (non-condensing)
	Operating temperature	-10°C ~55°C
	Storage temperature	-15°C ~60°C

*Product specifications are subject to change without further notice