

ECO Series

(1000VA)



Model Specification	1000VA
Rated inputcurrent/A	5A
Input voltage	95-270V
Output voltage	220V
Stability accuracy	±10%
Frequency	50Hz
Product color	White+Blue
Control type	Relay
Delay time	Short Delay:3-5secs Long delay:3-7mins
Protection	Overvoltage protection, over temperature protection, overload protection, short circuit protection
Over voltage	246V±4
Over temperature	125°C±10°C
Resistance	500MΩ
Voltage regulation speed	≤30ms
Waveform distortion	≤1%
Relative humidity	≤90%
Efficiency	≥95%
Levels of protection	IP20
Poster height	≤4000m
Display	LED Screen
Input	Euro plug
Output	Universal three-hole socket
Pcs/Carton	4
Product size (CM)	22.5×14.2×11.2
Packing size (CM)	32×31.5×29.6
N.W.(KGS)	3.3
G.W.(KGS)	15



Search for EcoShield in Google



+964776 675 5041

<https://www.ecoshieldfi.com>

Office Address

Finland Office: Vanha, Helsingintie, 18 B00700 Helsinki, Finland, Helsinkiiranta, Finland

Iraq Office: EcoShield Building, Al Senaha St, Baghdad, Baghdad Governorate

