

ECO Series

(10000VA)



Model Specification	10000VA
Rated inputcurrent/A	50A
Input voltage	95-270V
Output voltage	220V
Stability accuracy	±10%
Frequency	50Hz
Product color	White+Blue
Control type	Relay
Dekey time	Short Delay:3-5secs Long delay:3-7mins
Protection	Overvoltage protection, over temperature protection, overload protection, short circuit protection
Over voltage	246V±4
Over tem perature	125°C±10°C
Resistance	500MΩ
Voltage regulation speed	≤30ms
Waveform distortion	≤1%
Relative humidity	≤90%
Efficiency	≥95%
Levels of protection	IP20
Poster height	≤4000m
Display	LED Screen
Input	Terminal block
Output	Terminal block
Pcs/Cartron	1
Product size (CM)	40.8×28.5×18.3
Packing size (CM)	46.2×33.5×23.5
N.W.(KGS)	16.8
G.W.(KGS)	17.8



اريد ان اطلب المنتج من الشركة



+964776 675 5041



<https://www.ecoshieldfi.com>

Office Address

Finland Office: Vanha, Helsingintie, 18 000700 Helsinki, Finland, Helsinki, Finland

Iraq Office: EcoShield Building, Al Senaha St, Baghdad, Baghdad Governorate

